

REMARKS

It is believed that no fees are due for filing this Supplemental Amendment and Response.

In the event that a telephone conversation would further prosecution and/or expedite allowance, the Examiner is invited to contact the undersigned attorney at (760) 458-1863.

Respectfully Submitted,

By: 

Mark H. Snyder, Esq.
375 Walnut Avenue
Unit E
Carlsbad, CA 92008
(760) 458-1863

Date: 4 March 2003

Version With Markings To Show Changes Made

~~SEC 1. (Once Amended) A device for a moving vehicle having an~~
~~[protecting the] interior seat, seat back and foot well [of a~~
~~moving vehicle] for protecting said interior seat, seat back and~~
~~foot well from being soiled by a child in a safety seat,~~
s comprising:

B1
a mat having a perimeter and having a conformal surface for
placement between a safety seat having a base and a lateral
confinement, and said seat of the vehicle, said mat having a
10 lateral dimension and a longitudinal dimension, wherein said mat
lateral dimension extends beyond the lateral confinement of said
safety seat and has a flange outwardly extending at least 1 inch
from said conformal surface and around at least a portion of the
perimeter of said mat to define a containment area for
15 containment of liquid spills within said mat, and said mat
longitudinal dimension further extends beyond the base of said
safety seat and into said foot well.

Version With Markings To Show Changes Made

SJC 11. (Once Amended) A device for a moving vehicle having an
[protecting the] interior seat, seat back and foot well [of a
moving vehicle] for protecting said interior seat, seat back and
foot well from being soiled by a child in a safety seat,
5 comprising:

B2 a mat having a perimeter and having a conformal surface for
placement between a safety seat having a base and a lateral
confinement, and the seat of a vehicle, said mat having a lateral
10 dimension and a longitudinal dimension, wherein said mat lateral
dimension extends beyond the lateral confinement of said safety
seat at least 2 inches, and has a flange extending outwardly from
said mat surfaces at least 1 inch from said mat conformal
surface, said flange extending around the perimeter of said mat
15 to define a containment area for containment of liquid spills
within said mat, said mat also contains a pass-through for a
safety belt that maintains the integrity of said containment area
for containment of liquid spills within said mat.

Version With Markings To Show Changes Made

Sub 17. (Once Amended) A device for a moving vehicle having an
[protecting the] interior seat, seat back and foot well, said
foot well having horizontal and vertical surfaces [of the foot
5 well of a moving vehicle], for protecting said interior seat,
seat back, and foot well surfaces from being soiled by a child in
a safety seat, comprising:

B3
a mat having a perimeter and having a conformal surface for
10 placement between a safety seat having a base and a lateral
confinement, and the seat of a vehicle, said mat having a flange
extending outwardly at least 1 inch from said mat conformal
surface, said flange extending around at least a portion of the
perimeter of said mat to define a containment area for
15 containment of liquid spills within said mat, and said conformal
surface of said mat includes a horizontal portion that conforms
to said seat, a vertical portion that conforms to said vertical
foot well surface, and a horizontal portion that conforms to said
horizontal foot well surface.